

Stainless Steel Washdown Bench Scale



Model	PS-3000	PS-6000	PS-12K	PS-30K
Capacity	3,000 g / 6.6 lb	6,000 g / 13.2 lb	12 kg / 26.4 lb	30 kg / 66 lb
Readability	0.5 g / 0.001 lb	1 g / 0.002 lb	0.002 kg / 0.005 lb	0.005 kg / 0.01 lb
Divisions	6,000	6,000	6,000	6,000
Weighing Units / Functions	g / lb / lb : oz			
Stabilization Time (seconds)	< 1.5			
Tare Range	To capacity by subtraction			
Power Source	Built-in rechargeable battery or external power adapter (included)			
Construction	Stainless steel platform, pillar, indicator and housing			
Display	1 inch (25.4 mm) wide viewing angle LCD			
Platform Size (w x h x d)	11 x 3.7 x 13 inches / 280 x 95 x 330 mm			
Dimensions (w x h x d)	11 x 17.9 x 13 inches / 280 x 455 x 330 mm			
Operating Environment	32° ~ 104° F non condensing R.H. ≤ 85%			
Net Weight	15.6 lb / 7.1 kg			
Shipping Weight	18.3 lb / 8.3 kg			
Nema / IP Rating	IP 65			
Options	EL backlight, RS232C interface (waterproof)			

Features

- Stainless steel platform, pillar, indicator and housing
- Heavy duty construction
- Sealed electronics
- Low profile
- Reads in grams, pounds and pounds : ounces
- Built-in rechargeable battery or external power adapter
- Accumulation function
- Zero tracking
- Automatic power save
- Low battery indicator / charge status indicator
- Auto-calibration function
- Adjustable stainless steel feet with rubber inserts
- Wide angle LCD display

Benefits

- Easy to clean for food processing or harsh environments / washdown resistant
- Will withstand harsh industrial operation
- Improved water and dust resistance
- Easy to load and unload platform only 3.74 inches / 95 mm high
- Flexibility of operation
- Portability - battery lasts a minimum of 100 hours
- Allows you to add together consecutive weights to arrive at a total
- Assures that you always start weighing at zero
- Conserves battery power
- Alerts you to charge the battery, saving downtime
- Ensures accuracy
- Balance remains level for accurate results on uneven working surfaces - Anti-slip
- Can be seen from a wide viewing angle



Call:
1-800-836-8445